

Technical Specs BMW R 12 G/S.

		R 12 G/S
Engine		
Capacity	CC	1,170
Bore/stroke	mm	101 x 73
Output	kW/hp	80/109
at engine speed	rpm	7,000
Torque	Nm	115
at engine speed	rpm	6,500
Туре		Water-cooled, 2-cylinder, four-stroke boxer engine with four valves per cylinder operated by cam followers and two overhead camshafts per cylinder
Compression		12
Fuel		Premium unleaded 95 RON
Valves per cylinder		4
Ø intake/outlet	mm	39/33
Ø throttle valve	mm	50
Engine control		BMS-O
Emission control		Closed-loop three-way catalytic converter, exhaust standard EU-5+
Electrical system		
Generator	W	660
Battery	V/Ah	12/12 maintenance-free
Headlight		LED
Rear light		LED
Turn indicators		LED
Starter	W	1200
Power transmission		
Clutch		Dry clutch, hydraulically operated
Transmission		Claw-shift 6-speed gearbox
Primary ratio		1.737
Transmission ratios		2.375
	<u> </u>	
	<u> </u>	1.696
	 	1.296
	IV	1.065
	V	0.939
Considerate delica	VI	0.848
Secondary drive		Universal shaft
Secondary ratio		2.91

		R 12 G/S
Chassis		
Frame construction type		Tubular space frame in steel, engine self-supporting
Front wheel suspension		JSD telescopic forks, spring base, rebound and compression damping adjustable Ø 45 mm
Rear wheel suspension		Aluminum Paralever swinging arm, directly linked WAD spring strut, spring base, rebound and compression damping adjustable
Spring travel, front/rear	mm	210/200
Wheel castor	mm	120.8 / 121.3 (Enduro Package Pro)
Wheelbase	mm	1,580 / 1,585 (Enduro Package Pro)
Steering head angle	0	63.1 / 63.2 (Enduro Package Pro)
Brakes	front	Twin disc brake with two axially bolted 2-piston floating calipers, Ø 310 mm.
	rear	Single disc brake, Ø 265 mm, 2-piston floating caliper
ABS		Standard equipment BMW Motorrad ABS Pro (lean angle optimised)
Wheels		Aluminum cross-spoke wheels
	front	2.15 x 21"
	rear	4.00 x 17" / 4.00 x 18" (Enduro Package Pro)
Tires	front	90/90-21
	rear	150/70 R 17 / 150/70 R 18 (Enduro Package Pro)
Dimensions and weights		
Total length	mm	2,200
Overall width incl. hand levers	mm	830
Seat height	mm	860 / 875 (Enduro Package Pro)
DIN unladen weight, road ready	kg	229
Permitted total weight	kg	430
Fuel tank capacity	1	15.5
Performance figures		
Fuel consumption (WMTC)	l/100 km	5.1
CO2	g/km	119
Acceleration 0-100 km/h	S	4.1
Top speed	km/h	>200